

UB12E

EXPLOSION PROOF BLOWER

HIGH STATIC CAPACITY

SURE FLAME



Features:

- Heavy Duty 100% Steel Body – Built to Last
- Convenient Carry Handles
- CSA Certified for Hazardous Locations
 - Class 1, Group D
- Explosion Proof Switch
- Cord is Installed (Requires Explosion Proof Socket)
- Tubular Frame and Mounted Lifting Lug
- On / Off Switch with a 6 ft Cord
- Long Lasting with Fully Replaceable Parts
- Low Amp Draw
- Quiet Operation with High CFM Air Flow

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964

Specifications

Fan Rating	
2,900 cfm	
Static Pressure / CFM	
0" WC	2,930 cfm
0.5" WC	2,720 cfm
0.75" WC	2,590 cfm
1.0" WC	2,440 cfm
1.5" WC	2,050 cfm
1.75" WC	1,780 cfm
Power Requirements - 1 Ph	
115 V or 230V	
Max Amp Draw	
9.0 Amp	
Electric Motor	
1 hp	
Dimensions - LWH	
29" x 12" x 28"	
Weight	
80 lbs	37 kg

SAFE • TOUGH • RELIABLE

sureflame.ca