

# IX1500

INDIRECT HEATER 1.5 M BTU

PROPANE / NATURAL GAS

# SURE FLAME



## Features:

- 5-Year Pro-Rated Combustion Chamber Warranty
- 6 Heat Modes Controlled by the LED Control Panel
- Ductable for Maximum On-Site Flexibility
- 4 Outlet Options to put Heat Where it is Needed
- High Static System that will Duct up to 300'
- High Efficiency Unit Rated at 83%
- Great Heat Rise and Maximum Discharge Temperatures
- Easy-to-Use Diagnostics Panel that Records the Errors, Speeds up Troubleshooting, and Decreases Downtime – NO Reader Needed
- Compact Design that Helps on the Site and for Transport

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

# SURE FLAME

SINCE 1964



## Specifications\*

BTU / HR	
Maximum	1,500,000
Minimum	1,150,000
Efficiency	
83%	
Fan Rating	
20,500 cfm	
Heated Air Flow	
10,000 cfm @ 100 C	
Static Pressure	
High Static System	
Heat Modes	
High / Low / Off	High / Off
Low / Off	Cnst. On / High
Cnst. On / Low	Fan Only
Heat Rise	
70 to 120 C	125 to 215 F
Max Discharge Temp	
145 C	293 F
Outlet Sizing Options - Inches	
24" Square	24" Round
2 x 20" Round	4 x 20" Round
Max Duct Length	
300' +	91.5 m
Air Recirculation	
Yes	
Power Requirements - 3 Ph	
208/230 or 460 or 575 V	
Max Amp Draw	
208 V = 40 Amp	230 V = 38 Amp
460 V = 18 Amp	575 V = 14.4 Amp
Flue Diameter	
12" Std	
Fuel Type & Consumption	
Propane (lpg)	
596 cfh	68.4 lbs/hr
62.9 L/hr	16.6 gph (US)
Nat Gas = 1,456 cfh	
Gas Connection	
1 1/2" npt	
Dimensions - LWH	
114" x 32.5" x 77.5"	
Weight	
2,160 lbs	980 kg

\* Specifications are Approx and may be Altered Without Notification

SAFE • TOUGH • RELIABLE

sureflame.ca