

IX800

INDIRECT HEATER 800,000 BTU

PROPANE / NATURAL GAS

SURE FLAME



Specifications*

BTU / HR	
800,000 BTU / Hr	
Efficiency	
84%	
Fan Rating	
13,600	
Heated Air Flow	
7,000 cfm	
Static Pressure	
High Static System	
Heat Modes	
On / Off	Fan Only
Constant On - High	
Heat Rise	
80 to 133 C	144 to 259 F
Max Discharge Temp	
146 C	294 F
Outlet Sizing Options - Inches	
1 x 20" Round	2 x 16" Round
Max Duct Length	
300'	91.5 m
Air Recirculation	
Yes	
Power Requirements	
208/230 V - 1 or 3 Ph	
Max Amp Draw	
1 ph - 208 V = 43.6 Amp	
1 ph - 230 V = 39.4 Amp	
3 ph - 208 V = 27.0 Amp	
3 ph - 230 V = 24.4 Amp	
Flue Diameter	
8" Std	
Fuel Type & Consumption	
Propane (lpg)	
159 cfh	35.5 lbs/hr
33.6 L/hr	8.9 gph (US)
Nat Gas = 776.7 cfh	
Gas Connection	
1" npt	
Dimensions - LWH	
114" x 32.5" x 77.5"	
Weight	
1340 lbs	610 kg
* Specifications are Approx and may be Altered Without Notification	

Features:

- 5-Year Pro-Rated Combustion Chamber Warranty
- 3 Heat Modes Controlled by the LED Control Panel
- High Static System that will Duct up to 300' for Maximum On-Site Flexibility
- High Efficiency Unit Rated at 84%
- Great Heat Rise and Maximum Discharge Temperatures
- Easy-to-use Diagnostics Panel that Records Errors, Speeds up Troubleshooting and Decreases Downtime – NO Reader Needed
- Compact Design that Helps on the Site and During Shipping



Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964



SAFE • TOUGH • RELIABLE

sureflame.ca