

S100

DIRECT FIRED – 100,000 BTU

PROPANE / NATURAL GAS

SURE FLAME



Specifications*

BTU / HR	
100,000	
Efficiency	
99.9%	
Fan Rating	
1500 cfm	
Heat Modes	
On - Off	
Max Duct Length	
Non-Ductable	
Power Requirements - 1 Ph	
110 - 120 V	
Max Amp Draw	
4 Amp	
Fuel Type & Consumption	
Propane (lpg) - Only	
39.7 cfh	4.6 lbs/hr
4.2 L/hr	1.1 gph (US)
Nat Gas = 97.1 cfh	
Gas Connection	
1/2" npt	
Supply Pressure	
0.15 to 0.5 psi or 5 to 14" WC	
Dimensions - LWH	
25" x 14" x 18"	
Weight	
52 lbs	23.6 kg
* Specifications are Approx and may be Altered Without Notification	

Features:

- Great for Smaller Places in Various Situations
- Proven Reliability and Extremely Simple Design
- Easily Moved from Place to Place with a Convenient Handle
- Quiet Operation
- Simple Controls and Easy to Use with Spark Ignition
- Switch Easily Between Natural Gas and Propane
- Low Amperage Draw for any Situation
- Internally Mounted Fan to Move Heated Air Wherever Needed
- Compact Design Allows for Easy Storage
- Approved for Indoor Use

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964



SAFE • TOUGH • RELIABLE

sureflame.ca