

S1500E

DIRECT FIRED – 1.5 M BTU

PROPANE / NATURAL GAS

SURE FLAME



Features:

- Exceptional Performance and Long-Term Reliability
- High (1.5 M BTU) or Low (850 K BTU) Output Providing Flexibility for Almost any Project that Requires Heat
- Rugged and Simple Design Offering Years of Performance
- Safe Operation and Multiple Safety Controls
- Rent Ready with the Sure Flame Design
- Easy to use, Straightforward Operational Controls
- Stackable Storage Design for Decreased Footprint
- Movable Around the Job Site with Mounted Wheels
- Easily Switch between Natural Gas and Propane
- Standard Thermostat for More Control on any Job

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964



Specifications*

BTU / HR	
Maximum	1,500,000
Minimum	850,000
Efficiency	
99.9%	
Fan Rating	
7,000 cfm	
Heat Modes	
High / Low / Off - T-stat Controlled	
Max Duct Length	
Non-Ductable	
Power Requirements - 1 Ph	
120 V	
Max Amp Draw	
9.4 Amp	
Fuel Type & Consumption	
Propane (lpg)	
596 cfh	68.4 lbs/hr
62.9 L/hr	16.6 gph (US)
Nat Gas = 1,456 cfh	
Gas Connection	
1 1/2" npt	
Supply Pressure	
0.3 - 0.5 psi - 8 - 14" WC	
Dimensions - LWH	
63" x 31" x 39"	
Weight	
285 lbs	130 kg

* Specifications are Approx and may be Altered Without Notification

SAFE • TOUGH • RELIABLE

sureflame.ca