

S2200D

DIRECT FIRED – 2.2 M BTU

PROPANE / NATURAL GAS

SURE FLAME



Features:

- Built-in Flexibility for Heating Medium or Large Areas with Multiple Heating Modes
- Exceptional Performance Even in Make-up Air Applications
- High-Efficiency Fan for Job Sites That Require Ducting
- Easily Change to Different Heat Modes with the LED Control Panel
- LED Control Panel Stores Error Codes for Faster, Pinpointed Troubleshooting Resulting in Less Downtime – No Reader Needed
- Power Options Include 1 & 3 Phase
- Quickly Switch Between Natural Gas and LPG
- Easily Moved on the Job Site with Forklift Pockets and Lifting Lugs
- Stackable Design for Easy Storage

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964



Specifications*

BTU / HR	
Maximum	2,250,000
LPG - Minimum	1,950,000
Nat Gas - Minimum	1,650,000
Efficiency	
99.9%	
Fan Rating	
12,000	
Heat Modes	
High / Low / Off	High / Off
Low / Off	Cnst. On / High
Cnst. On / Low	Fan Only
Outlet Sizing Options - Inches	
24" Square Only	
Max Duct Length	
40' - Metal Only - 12.2 m	
Air Recirculation	
No	
Power Requirements - 1 or 3 Ph	
208/230 or 460 or 575 V	
Max Amp Draw	
1 ph - 208 V = 27.7 Amp	
1 ph - 230 V = 25.0 Amp	
3 ph - 208 V = 17.4 Amp	
3 ph - 230 V = 15.7 Amp	
3 ph - 460 V = 7.9 Amp	
3 ph - 575 V = 6.3 Amp	
Fuel Type & Consumption	
Propane (lpg)	
895 cfh	102.6 lbs/hr
99.4 L/hr	24.9 gph (US)
Nat Gas = 2,185 cfh	
Gas Connection	
1 1/2" npt	
Dimensions - LWH	
81" x 44" x 51"	
Weight	
810 lbs	367 kg
* Specifications are Approx and may be Altered Without Notification	

SAFE • TOUGH • RELIABLE

sureflame.ca