

SE410

HYBRID ENCLOSED FLAME

PROPANE / NATURAL GAS

SURE FLAME



Features:

- A Hybrid Design with NO VISIBLE FLAME
- Exceptional Performance and Reliability
- Combustion Monitoring that Self-Adjusts for Proper O² Levels
- Virtually *NO MEASURABLE CO* is Generated
- Keeps Discharge Air Safe for Workers
- Operates Between 250,000 and 400,000 BTU
- Ductable up to 75' to Put Heat Where it is Needed
- Very Cost-Effective with Nearly 100% Efficiency
- Easy-to-Use Diagnostics & Status Screen Simplifies Troubleshooting
- Easy to Use and Move with Stackable Design for Easy Storage
- Fold-Away Handle with Wheels
- Approved for Indoor and Outdoor Use

Call us: 1-800-661-1162

4115 – 18 Ave N, Lethbridge, AB T1H 5G1



1964 – 2025



Specifications*

BTU / HR	
Maximum	400,000
Minimum	250,000
Efficiency	
99%	
Fan Rating	
4,500 cfm	
Heated Air Flow	
2,400	
Static Pressure	
High Static System	
Heat Modes	
On / Off	Fan Only
Constant On	
Heat Rise	
95 C	171 F
Max Discharge Temp	
115 C	239 F
Outlet Sizing Options - Inches	
16" Round	2 x 12" Round
Max Duct Length	
75'	22.9 m
Air Recirculation	
No	
Power Requirements	
110 / 120 V - 1 Ph	
Max Amp Draw	
9.6 Amp	
Fuel Type & Consumption	
Propane (lpg)	
159 cfh	18.2 lbs/hr
16.8 L/hr	4.4 gph (US)
Nat Gas = 388.3 cfh	
Gas Connection	
1" npt	
Dimensions - LWH	
56" x 25" x 33"	
Weight	
250 lbs	113 kg
* Specifications are Approx and may be Altered Without Notification	

SAFE • TOUGH • RELIABLE

sureflame.ca