

S150 & 300

DIRECT FIRED

PROPANE - LPG ONLY

SURE FLAME



Specifications*	S150	S300	
BTU / HR	150,000	300,000	
Efficiency	99.9%	99.9%	
Fan Rating	FN2 Fan optional - 1500 cfm		
Heat Modes	On - Off	On - Off	
Max Duct Length	Non-Ductable	Non-Ductable	
Power Requirements	No Power Required		
Fuel Type & Consumption	Propane (lpg) - Only 59.6 cfh 6.8 lbs/hr 6.3 L/hr 1.7 gph (US)	Propane (lpg) - Only 119.2 cfh 13.7 lbs/hr 12.6 L/hr 3.3 gph (US)	
Gas Connection	POL		
Supply Pressure	Tank Pressure to Regulator		
Dimensions - LWH	37" x 13" x 16.5"	43.5" x 19" x 22.5"	
Weight	32 lbs	45	
	14.5 kg	20 kg	
	* Specs are Approx & may be Altered Without Notification		

Features:

- Great for Smaller Places in Various Situations
- 2 Different BTU Outputs Depending on the Job Size
- Designed for Sites that have NO POWER Available
- Proven Reliability and Extremely Simple Design
- Easily Moved from Place to Place with a Convenient Handle
- Simple Controls, Quiet Operation, and Easy to Use
- Compact Design Allows for Easy Storage
- Approved for Indoor Use
- Come with 15' Hose, Regulator & POL for Bottle Hook-Up



Call us: 1-800-661-1162



4115 - 18 Ave N,
Lethbridge, AB T1H 5G1

SURE FLAME

SINCE 1964

SAFE • TOUGH • RELIABLE

sureflame.ca