

# ID4

**INDIRECT HEATER – 400,000 BTU**

**DIESEL, KEROSENE, #2 FUEL OIL**

# SURE FLAME



### Features:

- 5-Year Pro-Rated Combustion Chamber Warranty
- 3 Heat Modes Controlled by the LED Control Panel
- Ductable for 100' for both 16" or 2 x 12"
- Fantastic Heat Rise and a Great Discharge Temperature
- Low Amperage Draw for Construction Sites
- Narrow Design - Fits Through Doorways
- Standard Tigerloop Fuel De-Aerator
- Easy-to-use Diagnostics Panel that Records the Errors, Speeds up Troubleshooting, and Decreases Downtime – No Reader Needed
- Easy to Move on the Site with Lifting Lug and Fork Lift Pockets
- Ergonomic Fold-Away Handle with Foam-Filled Wheels and Good Balance for One Person Handling
- Large Metal Fuel Tank for Years of Life

**Call us: 1-800-661-1162**

4115 – 18 Ave N, Lethbridge, AB T1H 5G1



**SINCE 1964**



### Specifications\*

<b>BTU / HR</b>	
400,000	
<b>Efficiency</b>	
82%	
<b>Fan Rating</b>	
5,000 cfm	
<b>Heated Air Flow</b>	
2,410	
<b>Static Pressure</b>	
High Static System	
<b>Heat Modes</b>	
On / Off	Fan Only
Constant On - High	
<b>Heat Rise</b>	
80 to 120 C	145 to 215 F
<b>Max Discharge Temp</b>	
129 C	264 F
<b>Outlet Sizing Options - Inches</b>	
16" Round	2 x 12" Round
<b>Max Duct Length</b>	
100'	30.5 m
<b>Air Recirculation</b>	
Yes	
<b>Power Requirements - 1 Ph</b>	
110 / 120 V - 1 Ph	
<b>Max Amp Draw</b>	
12.0 Amp - 10.5 Amp Operational	
<b>Flue Diameter</b>	
6"	
<b>Fuel Type</b>	
Diesel, Kerosene, #2 Fuel Oil	
<b>Fuel Consumption</b>	
Min = 8.1 L/hr or 2.15 US g/hr	
Max = 10.9 L/hr or 2.87 US g/hr	
<b>Fuel Tank Capacity</b>	
160 L - 42.2 US Gal	
<b>Dimensions - LWH</b>	
77" x 30" x 58"	
<b>Weight</b>	
630 lbs	240 kg
* Specifications are Approx and may be Altered Without Notification	

**SAFE • TOUGH • RELIABLE**

**sureflame.ca**